

## PRODUCT DATA

# NSRFL

	<u>SUBSTANCE</u>		<u>THICKNESS</u>
Adhesive	16gsm	Adhesive	16 micron
Liner	65gsm	Liner	55 micron

### PRODUCT DESCRIPTION

A peelable carrier free transfer tape with an acrylic based adhesive. The liner is a two sided release system which overlaps at each edge to give a 'fingerlift' product for easy removal.

### APPLICATIONS

Ideal for 'point of sale' displays such as window posters, advertising materials and business forms requiring a low tack removable adhesive system. The transparent adhesive allows mounting inside windows without obscuring display. The tape is also suitable for some re-sealable polythene bags and other applications where ease of removability is required, however the user should carry out suitability tests before use.

<u>ADHESIVE PROPERTIES</u>	<u>20 min</u>	<u>24 hour</u>	<u>TEST METHOD</u>
Adhesion to steel	100N/M	150N/M	BS7116:1990 - D
Shear Adhesion	25 hours		BS7116:1990 - B
Release of liner from adhesive	5 N/M		BS7116:1990 - E

### THERMAL PROPERTIES

Recommended service temperature range	-20°C to 70°C
Application temperature range	10°C to 50°C

### SHELF LIFE

Minimum shelf life when stored in closed cartons away from direct sources of heat and sunlight.	1 year
---	--------